

Sealed Lead-Acid Batteries

	Model: 6SB1.3P Voltage: 6V Capacity: 1.3Ah (C20) Int. resistance: 70 mOhm	Max charge I: 0.3 Amps Max discharge I: 36 Amps (5 sec) Cyclic charge Volts: 7.35 to 7.5V Standby charge Volts: 6.75 to 6.9V
	Length: 96.5mm. Width: 23.5mm. Height: 51mm (57mm). Weight: 0.3kg. Units per box: 40.	
	Model: 6SB3.2S Voltage: 6V Capacity: 3.2Ah (C20) Int. resistance: 30 mOhm	Max charge I: 0.65 Amps Max discharge I: 70 Amps (5 sec) Cyclic charge Volts: 7.35 to 7.5V Standby charge Volts: 6.75 to 6.9V
	Length: 66mm. Width: 33mm. Height: 100mm (107mm). Weight: 0.64kg. Units per box: 20.	
	Model: 6SB3.2P Voltage: 6V Capacity: 3.2Ah (C20) Int. resistance: 30 mOhm	Max charge I: 0.65 Amps Max discharge I: 70 Amps (5 sec) Cyclic charge Volts: 7.35 to 7.5V Standby charge Volts: 6.75 to 6.9V
	Length: 134mm. Width: 33mm. Height: 60mm (66mm). Weight: 0.64kg. Units per box: 20.	
	Model: 6SB4R25P Voltage: 6V Capacity: 5Ah (C20) Int. resistance: 20 mOhm	Max charge I: 0.9 Amps Max discharge I: 75 Amps (5 sec) Cyclic charge Volts: 7.35 to 7.5V Standby charge Volts: 6.75 to 6.9V
	Length: 67mm. Width: 67mm. Height: 97mm (110mm). Weight: 0.95kg. Units per box: 10.	
	Model: 6SB4.5P Voltage: 6V Capacity: 4.5Ah (C20) Int. resistance: 18 mOhm	Max charge I: 0.3 Amps Max discharge I: 36 Amps (5 sec) Cyclic charge Volts: 7.35 to 7.5V Standby charge Volts: 6.75 to 6.9V
	Length: 70mm. Width: 46mm. Height: 102mm (108mm). Weight: 0.82kg. Units per box: 20.	
	Model: 6SB7.2P Voltage: 6V Capacity: 7.2Ah (C20) Int. resistance: 13 mOhm	Max charge I: 1.5 Amps Max discharge I: 105 Amps (5 sec) Cyclic charge Volts: 7.35 to 7.5V Standby charge Volts: 6.75 to 6.9V
	Length: 150mm. Width: 34mm. Height: 94mm (100mm). Weight: 1.25kg. Units per box: 16.	
	Model: 6SB12P Voltage: 6V Capacity: 12Ah (C20) Int. resistance: 10 mOhm	Max charge I: 2.4 Amps Max discharge I: 180 Amps (5 sec) Cyclic charge Volts: 7.35 to 7.5V Standby charge Volts: 6.75 to 6.9V
	Length: 151mm. Width: 50mm. Height: 93.5mm (99.5mm). Weight: 2kg. Units per box: 10.	

Sealed Lead-Acid Batteries

	Model: 12SB1.3P Voltage: 12V Capacity: 1.3Ah (C20) Int. resistance: 130 mOhm	Max charge I: 0.3 Amps Max discharge I: 36 Amps (5 sec) Cyclic charge Volts: 14.7 to 15V Standby charge Volts: 13.5 to 13.8V
	Length: 96.5mm. Width: 45mm. Height: 53mm (59mm). Weight: 0.3kg. Units per box: 20.	
	Model: 12SB2.2P Voltage: 12V Capacity: 2.2Ah (C20) Int. resistance: 90 mOhm	Max charge I: 0.5 Amps Max discharge I: 60 Amps (5 sec) Cyclic charge Volts: 14.7 to 15V Standby charge Volts: 13.5 to 13.8V
	Length: 178mm. Width: 34mm. Height: 60mm (66mm). Weight: 0.83kg. Units per box: 20.	
	Model: 12SB3.3P Voltage: 12V Capacity: 3.3Ah (C20) Int. resistance: 60 mOhm	Max charge I: 0.7 Amps Max discharge I: 60 Amps (5 sec) Cyclic charge Volts: 14.7 to 15V Standby charge Volts: 13.5 to 13.8V
	Length: 134mm. Width: 67mm. Height: 61mm (67mm). Weight: 1.29kg. Units per box: 10.	
	Model: 12SB5P Voltage: 12V Capacity: 5Ah (C20) Int. resistance: 40 mOhm	Max charge I: 1 Amps Max discharge I: 75 Amps (5 sec) Cyclic charge Volts: 14.7 to 15V Standby charge Volts: 13.5 to 13.8V
	Length: 90mm. Width: 70mm. Height: 101mm (107mm). Weight: 1.6kg. Units per box: 10.	
	Model: 12SB7.2P Voltage: 12V Capacity: 7.2Ah (C20) Int. resistance: 25 mOhm	Max charge I: 1.5 Amps Max discharge I: 105 Amps (5 sec) Cyclic charge Volts: 14.7 to 15V Standby charge Volts: 13.5 to 13.8V
	Length: 150mm. Width: 64.5mm. Height: 96mm (101mm). Weight: 2.5kg. Units per box: 8 or 10. Available with standard faston 187 terminal (4.75mm wide) or faston 250 terminal (6.35mm wide)	
	Model: 12SB12P Voltage: 12V Capacity: 12Ah (C20) Int. resistance: 30 mOhm	Max charge I: 2.4 Amps Max discharge I: 180 Amps (5 sec) Cyclic charge Volts: 14.7 to 15V Standby charge Volts: 13.5 to 13.8V
	Length: 151mm. Width: 97.5mm. Height: 96mm (102mm). Weight: 3.95kg. Units per box: 4.	
	Model: 12SB18P Voltage: 12V Capacity: 18Ah (C20) Int. resistance: 14 mOhm	Max charge I: 3.6 Amps Max discharge I: 250 Amps (5 sec) Cyclic charge Volts: 14.7 to 15V Standby charge Volts: 13.5 to 13.8V
	Length: 180mm. Width: 76mm. Height: 167mm (167mm). Weight: 5.96kg. Units per box: 2.	
	Model: 12SB26P Voltage: 12V Capacity: 26Ah (C20) Int. resistance: 12 mOhm	Max charge I: 5 Amps Max discharge I: 288 Amps (5 sec) Cyclic charge Volts: 14.7 to 15V Standby charge Volts: 13.5 to 13.8V
	Length: 165mm. Width: 175mm. Height: 125mm (125mm). Weight: 8.52kg. Units per box: 1.	

Sealed Lead-Acid Batteries

	Model: 12SB33P Voltage: 12V Capacity: 33Ah (C20) Int. resistance: 9 mOhm	Max charge I: 6.5 Amps Max discharge I: 330 Amps (5 sec) Cyclic charge Volts: 14.7 to 15V Standby charge Volts: 13.5 to 13.8V
Length: 194mm. Width: 130mm. Height: 167mm (167mm). Weight: 12kg. Units per box: 1.		
	Model: 12SB44P Voltage: 12V Capacity: 44Ah (C20) Int. resistance: 6 mOhm	Max charge I: 9 Amps Max discharge I: 500 Amps (5 sec) Cyclic charge Volts: 14.7 to 15V Standby charge Volts: 13.5 to 13.8V
Length: 196mm. Width: 164mm. Height: 171mm (171mm). Weight: 14kg. Units per box: 1.		
	Model: 12SB70P Voltage: 12V Capacity: 70Ah (C20) Int. resistance: 5.5 mOhm	Max charge I: 14 Amps Max discharge I: 800 Amps (5 sec) Cyclic charge Volts: 14.7 to 15V Standby charge Volts: 13.5 to 13.8V
Length: Version 1. Length: 350mm. Width: 166mm. Height: 174mm (174mm). Weight: 25kg. 1 per box Version 2. Length: 257mm Width: 166mm. Height: 214mm (214mm). Weight: 25kg. 1 per box		
	Model: 12SB100P Voltage: 12V Capacity: 100Ah (C20) Int. resistance: 3.9 mOhm	Max charge I: 20 Amps Max discharge I: 900 Amps (5 sec) Cyclic charge Volts: 14.7 to 15V Standby charge Volts: 13.5 to 13.8V
Length: 304mm. Width: 166mm. Height: 214mm (214mm). Weight: 30kg. Units per box: 1.		
	Model: 12SB120P Voltage: 12V Capacity: 120Ah (C20) Int. resistance: 3.1 mOhm	Max charge I: 24 Amps Max discharge I: 1100 Amps (5 sec) Cyclic charge Volts: 14.7 to 15V Standby charge Volts: 13.5 to 13.8V
Length: 406mm. Width: 172mm. Height: 234mm (234mm). Weight: 39kg. Units per box: 1.		
	Model: BR100 (6TL) Voltage: 12V Capacity: 100Ah (C5 to 9V 27°C)	DIN standard VG 96924-2 NSN: 6140-12-190-9027
Length: 284mm. Width: 267mm. Height: 230mm. Weight: 39.5kg. Military vehicle applications (leopard tank and others)		